

PAINT & GASKET REMOVER SPRAY

For Fast Removal of Paints, Gaskets Adhesives without Excessive Scraping

Product Description

ASV® Paint & Gasket Remover is a fast acting blend of solvents for removal of paints, gaskets, adhesives, sealants, lacquers and varnishes without excessive scraping or causing damage to the surfaces. It also cleans stubborn grease, oil, varnish and carbon deposits.

Applications

- For removal of baked-on gaskets, gasket cements and formed-in place types of gaskets.
- For removal of paint, adhesives, lacquers and varnishes without excessive scraping or causing damage to the surfaces.
- For cleaning stubborn grease, oil, varnish, carbon
- deposits.

Benefits

- Removes gaskets, paints, sealants, varnishes
- Fast acting formula cleans dried grease & oil
- Protects surface finish from excessive scraping

Directions for Use

Mask areas not requiring removal or for protection from overspray. Observe precautions of wearing protective eyewear and hand gloves while handling this product. Spray liberally over surface and allow solvents 5-10 minutes to work for softening paint and then remove with a putty knife or cloth rag. For stubborn or thick coatings, repeat the same procedure.

To prevent clogging of actuator and valve dip-tube after use, invert the can and press the actuator button for a short burst till only clear propellant gas comes out.

Caution : Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

PAINT & GASKET REMOVER

SPRAY

TECHNICAL PROPERTY

Parameter*	Value
Type	Cleaner
Appearance	Viscous liquid
Color	Milky White
Odor	Solvent
Specific Gravity @ 20°C	1.05-1.25
Flash Point	-18°C (aerosol)
Solubility	Nil in water
Vapor Density (air = 1)	> air
Evaporation Rate	Faster than n-butyl acetate
Propellant	Non CFC

* of active ingredients

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

Available Packaging

500 ml aerosol spray

Shelf Life

24 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.